

**40V Max Brushless
230mm (9") Power Cut**



HEAVY DUTY BRUSHLESS

CE003G



Product Statement



HEAVY DUTY BRUSHLESS

40V Max Brushless 230mm (9") Power Cut

Introducing the Makita CE003G 40V Max Brushless 230mm (9") Power Cut, engineered for superior performance and durability. Delivering cutting speeds up to 45% faster than its LXT counterpart, this tool ensures you can tackle the toughest tasks with unmatched efficiency.

Experience enhanced safety with Active Feedback Sensing Technology (AFT) that shuts down the tool in the event of kickback, along with an electric brake and anti-restart function for advanced protection. The constant speed control and integrated overload indicator keep you informed and maintain optimal performance, even under heavy load. Designed with IPX4 weather-resistant construction, the CE003G is built to withstand harsh conditions, promising long-lasting reliability.

For unparalleled power, safety, and durability in your cutting tasks the Makita CE003G has you covered.



Product Overview



Product Specifications



Wheel Diameter	230mm (9")
Max. Cutting Depth	88mm
No load speed	6,600rpm
Noise	116dB
Vibration	3.0m/s ²
Overall length	603mm
Skin weight	5.5kg
Weight (with battery)	6.5kg (BL4040)
Voltage	40V Max

- **High Power** – high power brushless XGT motor delivers cutting speed up to 45% faster than the LXT equivalent.
- **Constant speed control** – maintains blade speed under load to increase cutting speed and performance.
- **LED Joblight** – for improved visibility in low light environments with a manual On & Off switch.
- **Water supply connection** – enables water supply to be connected to the tool for water suppression during masonry cuts, with hose running inside housing, reducing risk of being caught on objects on the jobsite.
- **Electric brake** – quickly stops the wheel rotation after the switch has been disengaged, ensuring safety through all stages of operation of the tool.
- **Overload Indicator** – alerts the user of overload on the tool with a blinking red LED light. Reducing load will increase performance and runtime.
- **Rotatable guard** – work position of the guard can be adjusted to better suit the working posture.
- **Active Feedback sensing Technology (AFT)** – automatically shuts down the tool as soon as kickback is sensed, providing increased protection during operation of the tool.
- **IPX4 Rated** – ingress protection rating IPX4 provides enhanced protection against water, allowing the tool to be used when wet and ensuring the longevity of the tool.

Advantages



Power



Up to 45% faster cutting than the LXT equivalent.

Safety



Active Feedback sensing Technology and electric brake

Innovation



Anti- Vibration Housing
Spring absorption reduces transferred vibration

Durability



Ingress protection rating IPX4 provides enhanced protection against water

Active Feedback sensing Technology (AFT)

The CE003G is equipped with Active Feedback sensing Technology – AFT.

AFT automatically shuts down the tool as soon as the rotation speed suddenly slows down and kickback is sensed, protecting the user from any risk and increasing safety during operation of the tool

AFT



Ingress Protection – IPX4

Ingress protection rating IPX4 provides enhanced protection against water, allowing the tool to be used when wet and ensuring the longevity of the tool.

In the IPX4 test the tool is sprayed from all directions. To pass the IPX4 test, the tool must go through the test without any harm at all.



Advantages



XGT Cutting Power

Up to

45%

More
Power

Test: Cut concrete continuously at a depth of 50mm, and measured the time required to cut across a 300mm wide

CE003G – 40V Max 5.0Ah – BL4050F (180Wh)
DCE090 – 18Vx2 6.0Ah – BL1860B (216Wh)



VS



XGT

LXT

Work Speed:

CE003G (19.5 seconds)

DCE090 (28.2 seconds)

Work Amount:

CE003G (BL4080F) 288Wh (16 cuts)

CE003G (BL4050F) 180Wh (10 cuts)

DCE090 (2x BL1860B) 216Wh (13 cuts)

Our Range



	CE001G	CE002G	CE003G	DCE090
				
Wheel Diameter	355mm (14")	355mm (14")	230mm (9")	230mm (9")
Max. Cutting Depth	127mm	127mm	88mm	88mm
No load speed	5,300rpm	4,200rpm	6,600rpm	6,600rpm
Noise	108.7dB	105.8dB	116dB	103dB
Vibration	2.0m/s ²	2.0m/s ²	3.0m/s ²	5.9m/s ²
Overall length	786mm	825mm	603mm	554mm
Skin weight	10.3kg	11.3kg	5.5kg	5.1kg
Weight (with battery)	14.1kg (2x BL4080F)	15.1kg (2x BL4080F)	6.5kg (BL4040)	6.3kg (2x BL1860B)
Voltage	80V Max (40Vx2)	80V Max (40Vx2)	40V Max	18Vx2 (36V)

Accessories


Standard Accessories

	123121-2	Hose fitting
	-	Box wrench
	-	Wrench Holder

Optional Accessories Specifically Designed for Cordless

	E-02967	Segmented Diamond Blade Multi Construction Cutting 230mm x 22.23 15mm Segment Height 2.4mm Thickness
	E-03006-25	Stainless Steel Cut Off Wheel 230mm x 2 x 22.23mm (25 Pack)

Optional Accessories

	988.394.610	Pressurized 10L Water Tank incl. hose & fittings
	B-15855	Quasar Diamond Blade Multi Construction Cutting 230mm x 22.23 12mm Segment / 3mm Thickness
	B-15970	Comet Diamond Blade Multi Construction Cutting 230mm x 22.23 10mm Segment / 3.2mm Thickness
	B-56281	Nebula Diamond Blade General Cutting 230mm x 22.23 10mm Segment / 2.4mm Thickness
	B-16053	Comet Turbo Diamond Blade Multi Construction Cutting 230mm x 22.23 8mm Segment / 2.4mm Thickness
	B-39718	Comet Diamond Blade Multi Construction Cutting 230mm x 22.23 5mm Segment / 1.6mm Thickness
	B-55326	Rescue Diamond Blade Multi Material Vacuum Brazed 230mm x 22.23 3.1mm Segment / 3.0mm Thickness